

EM 6/8/10 Combo Seamless Siding Machine



When you need more options, use the EM 6/8/10 Combo Seamless Siding Machine for the job. Make multiple profiles and widths with the standard package or purchase additional attachments for even more flexibility with just one machine. This machine features our self-contained embossing system that applies a natural woodgrain texture to the finished siding, adding strength and beauty.

STANDARD PROFILE ATTACHMENTS (Included with Machine)



Horizontal 6", 8", and 10"




Double 3", 4", and 5"



Double Dutch 4" and 5"

OPTIONAL PROFILE ATTACHMENTS




Dutch Lap 6", 8", and 10"



Colonial Dutch 4" and 5"



Board and Batten 6", 8", and 10"



Half Board and Batten 4" and 5"



Inverted Board and Batten 5"




Beaded Horizontal 6", 8", and 10"



Beaded Dutch 6", 8", and 10"



T1-11

Make it the last time you send your siding to the land fill. Recycle! 

► STANDARD PACKAGE

- EM 6/8/10 Combo Siding Machine
- Side Pull Guillotine Cutter
- 6 Adjustable Run-out Stands
- 10 Run-out Rails
- Cradle with 3 Coil Spools
- Standard Profile Attachments
- Horner ATM Control (Optional)
- Owner's Manual

► FEATURES

- Heavy-duty steel frame for structural stability and forming consistency
- Variable speed frequency drive
- Quick and easy profile conversion
- Industrial nitrocarburized rollers
- Extendable cutting table
- Multi-profile guillotine
- Emergency shut-off
- Chrome-plated shafts
- Spool brake
- Push button control with tethered remote control and 10 ft cord
- 5-year warranty*
- Operational training and technical support

► SPECIFICATIONS (as Shown)

MACHINE DIMENSIONS:

138 in. (L) x 33.5 in. (W) x 45 in. (H)

MACHINE WEIGHT:

2,975 lbs

COIL WIDTHS:

9 5/64 in., 10 5/8 in., or 13 1/4 in.

MATERIALS:

Steel: 26-29 ga

Aluminum: 0.024-0.027 in.

POWER:

1.5 HP, 110 V, Single Phase, 20 amps

OPERATIONAL SPEED:

Variable to 60 ft/min

FORMING STATIONS:

9

SHEAR/CUTTER:

Side Pull Guillotine

TRAILER & COIL LOADING SYSTEM

ENCLOSED TRAILER 16 FT TANDEM AXLE

This enclosed trailer includes an 8-foot fluorescent interior light, two 110-volt interior receptacles, a two-circuit panel with lifeline for a 110 volt, one heavy duty aluminum access ladder, and a 14-foot ladder rack and cat walk.



COIL LOADING SYSTEM NO FORKLIFT REQUIRED

Easily load coil without using a forklift. This cradle mounts to our EM 6/8/10 Combo Seamless Siding and EM 10 Snap Lock Roofing Machines and features a powerful 110-volt electric winch.



► TRAILER FEATURES

- Tandem 5,500 lb torsion axles (11,000 lb GVWR) 8-bolt hubs, 235R85/16E tires
- All-wheel electric brakes and breakaway kit
- 16 in. on-center construction, 2 in. (H) x 6 in. (W) box frame
- Adjustable tongue
- 24 in. tall aluminum tread plate
- Front stone guard
- 30 in. side door with camlock
- 3/4 in. solid-core plywood floor
- Walls lined in 3/8 in. plywood
- Insulated walls and ceiling
- Double rear swing out cargo doors (offset design)

► TRAILER SPECIFICATIONS

OVERALL LENGTH:

16 ft + 4 ft tongue

OVERALL HEIGHT:

8 ft

INTERIOR HEIGHT:

6 ft 6 in.

REAR RUN-OUT DOOR:

35 in. (W) x 20 in. (H)

CURBSIDE DOOR:

3 ft (W) x 6 ft (H)

EXTERIOR MATERIAL:

0.040 in. white aluminum