


EM 10 SNAP LOCK Roofing Machine



Eastside's portable EM 10 Snap Lock Roofing Machine is designed specifically for residential and light commercial applications. Its 9 3/4-inch rib-to-rib panel width gives it a look that belongs on your home, while other commercial roofing machines create panels that are not quite aesthetically correct.

This snap lock roofing machine runs 26–29 gauge steel coil for residential and light commercial applications. The strength of the panel is created in the snap lock design, and the concealed fastener system absorbs imperfections in your roof.

PROFILES



► STANDARD PACKAGE

- EM 10 Snap Lock Roofing Machine
- Geared Guillotine Cutter
- 4 Adjustable Run-out Stands
- 6 Run-out Rails
- Cradle with 3 Coil Spools
- Horner ATM Control *(Optional)*
- Owner's Manual

► FEATURES

- Heavy-duty steel frame for structural stability and forming consistency
- Variable speed frequency drive
- Industrial nitrocarburized rollers
- Nail slot punches
- Emergency shut-off
- Chrome-plated shafts
- Spool brake
- Tethered remote control and 10 ft cord
- 5-year warranty*
- Operational training and technical support

► SPECIFICATIONS *(as Shown)*

MACHINE DIMENSIONS:

88 in. (L) x 29 in. (W) x 20.5 in. (H)

MACHINE WEIGHT:

1,400 lbs

COIL WIDTHS:

13 1/4 in.

MATERIALS:

Steel: 26-29 ga

POWER:

2 HP, 110 V, Single Phase, 20 amps

OPERATIONAL SPEED:

Variable to 75 ft/min

FORMING STATIONS:

8

SHEAR/CUTTER:

Geared Guillotine

Make it the last time you send your roof to the land fill. Recycle! 

TRAILERS & COIL LOADING SYSTEM

ENCLOSED TRAILER 6 FT x 12 FT V-FRONT

Make your EM 10 Snap Lock Roofing Machine even more portable with a trailer. This v-nose enclosed trailer includes a 12-volt LED dome light, 50/50 rear swing-out door, curbside door with flush lock, radial tires, and more.



COIL LOADING SYSTEM NO FORKLIFT REQUIRED

Easily load coil without using a forklift. This cradle mounts to our EM 6/8/10 Combo Seamless Siding and EM 10 Snap Lock Roofing Machines and features a powerful 110-volt electric winch.



► TRAILER FEATURES

- 2-3,500 lb spring axles with electric brakes
- 15 in. radial tires
- V-nose
- One-piece aluminum roof
- 50/50 rear swing-out door
- 3 ft x 6 ft curbside door with flush lock
- 2 ft stone guard
- 12 V LED dome light

► TRAILER SPECIFICATIONS

OVERALL LENGTH:

12 ft + 18 in. v-nose + 30 in. tongue

EXTERIOR WIDTH:

6 ft

OVERALL HEIGHT:

8 ft

INTERIOR HEIGHT:

6 ft 6 in.

CURBSIDE DOOR:

3 ft (W) x 6 ft (H)

EXTERIOR MATERIAL:

0.030 in. white aluminum